

Release Notes

Public Release

Version 1.0.22	
Features	<ul style="list-style-type: none">Added hostname information to the System sta command.Added the ability to change the hostname in the web server.Added Velocity database of RS-232 and TCP commands for display control.Added the DispBtn command to the API.Added new Atlona logo to web server.
Bug Fixes	<ul style="list-style-type: none">Set HDMI as default input after executing the Mreset command.Renamed “Input 1” and “Input 2”, within the web server, to “HDMI” and “USB- Type C”, respectively.Removed feedback verify from display control.Fixed an issue where if HDCP is set to OFF, and the AT-OME-TX21-WP-E loses power, a black screen would sometimes be displayed, requiring HDCP to be turn ON and then back to OFF, in order to resolve the issue.Fixed an issue where sending the Display On command, when the display was already powered, would cause the video image to blink.Fixed an issue where sending the Display Off command over Telnet, would occasionally cause the AT-OME-TX21-WP-E to lock up, requiring the unit to be power-cycled.Fixed an issue where the RS-232 Zone settings would be lost after power-cycling the unit.Fixed an issue where the web server login password would accept derivations of the original password.
Known Issues	<ul style="list-style-type: none">None

Previous Releases

Version 1	
	<ul style="list-style-type: none">Factory firmware.